

IN THE SPECIFICATION:

Kindly replace the following first two paragraphs of page 7 of the specification with the respectively identified paragraphs below which have been marked up in accordance with 37 CFR 1.121 to show changes made relative to the immediate prior version as follows:

*In the first paragraph of page 7, the entirety of which begins at line 1, and concludes at line 7 of the same page, replace said paragraph with the following replacement paragraph:*

Turning now to Fig. 2 there is shown an alternate commode 10 and since many of the components are similar or the same as in the Fig. 1 embodiment, like numbers have been used for like components. In this embodiment, however, the ~~[[30]]~~ 30' is slid into and out of its operative position beneath the commode seat 40 by a downward L-shaped flange 44 beneath and extending along the lateral sides of the elongated opening 42 in the commode seat 40. Thus, rather than lifting the commode seat up to remove the pan ~~[[30]]~~ 30', it is convenient to install and remove the pan ~~[[30]]~~ 30' by simply sliding it into and out of its contiguous position beneath the elongated opening 42.

*In the second paragraph of page 7, the entirety of which begins at line 8, and concludes at line 18 of the same page, replace said paragraph with the following replacement paragraph:*

Turning now to Figs 3A and 3B, there are shown, side views, partly in section,

showing the 30, 30' of the present invention. In the Fig. 3A embodiment, it can be seen that the circular bottom 36 is a solid bottom and therefor the pan 30 is intended for use as a stand alone commode with the pan as a pail to collect and retain the waste materials. In the Fig. 3B embodiment, there is an opening at 45 in the circular bottom 36 of pan 30' and that embodiment is intended for use where the commode is located over a household toilet that the waste material is discharged directly into the toilet. As also seen in both Fig. 3A and 3B, the front surface 38 of the pan 30' curves downwardly and the circular bottom 45 is displaced rearwardly with respect to the midpoint of the length dimension L so that the pan 30' can be used with an elongated opening in the commode seat and the curved front surface 38 can direct the waste products rearwardly to the center of the household toilet for discharge into that system.